

HDM-1 multi HDMI modulator to DVB-T/C



Vhod s prehodom - za povezavo z zunanjimi viri signala. Naprava je prilagodljiva in lahko obdeluje HDMI signale iz sprejemnikov, računalnikov, kamer, DVD predvajalnikov in številnih drugih naprav. Modulator deluje s priloženo napajalno enoto.

A loop-through input is available for connection with external signal sources. The device is flexible and can process HDMI signals from receivers, computers, cameras, DVD players and many other devices. The modulator is operated with the supplied plug-in power supply unit.

Type	HDM-1 multi				
Article no.	20564				
HDMI input					
Video resolution	1920*1080_50/60p, 1920*1080_50/60i, 1440*576_50i, 1440*480_60i, 1280*720_50/60p, 720*576_50p, 720*480_60p, 640*480_60p				
Video encoding	H.264 / MPEG-4 AVC				
Audio encoding	MPEG1 Layer II / AAC				
Connector type	HDMI Typ A				
RF input					
Frequency range	5...1218 MHz				
Through loss	2 dB				
RF output					
Modulated channel frequency	174...1218 MHz				
Output level	59...99 dB μ V (adjustable)				
MER	= 38 dB				
Output modulation	DVB-T	DVB-C	ATSC-T	ATSC-C	DTMB
Bit rate Mbps	2...23	2...23	2...15	2...23	2...23
Channel bandwidth	6, 7 oder / or 8 MHz	2...8 MHz	6 MHz	6 MHz	8 MHz
Constellation	QPSK	16QAM	8VSB	64QAM	QPSK
	16QAM	32QAM		256QAM	QAM-4NR
	64QAM	64 QAM			16QAM
		128QAM			32QAM
		256QAM			64QAM
Power consumption	6 W max.				
Operating voltage (ext. power supply)	12 VDC				
Weight	0,6 kg				
Dimensions (W x H x D)	155 x 120 x 60 mm				