

# WISI GIMLP 4

INCA Multiscreen Launch Platform: Transcode, Segment and Package up to 4 HD or 8 SD Sources into HLS



**ELPAS**



## Description

The WISI Multiscreen Launch Platform is an all-in-one carrier-grade transcoder, live-streaming packager and origin server for high-value Internet video services. Transcode, segment and package up to 4 HD or 8 SD sources into HLS and serve up to 2 Gbps to downstream client devices. This affordable and efficient 1 RU solution includes automatic packager configuration for simple set-up with regular feature updates.

## At a glance:

- Transcode and stream live content on your network
- Stream to set-top boxes, TVs, smartphones and tablets
- Receive off-air sources and deliver them to multiscreen devices using WISI Chameleon or Tangram
- Enjoy powerful VidiOS™ management and troubleshooting tools with video thumbnails, stream capture and download, extensive statistical analysis, and stream logging
- Experience streamlined OTT deployment with Katamaran™

**WISI Communications GmbH & Co. KG**

Wilhelm-Sihn-Str. 5-7  
75223 Niefern - Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350  
E-Mail: [export@wisi.de](mailto:export@wisi.de)

Technical Modifications reserved. WISI cannot be held liable for any printing error. 24. November 2017, 9:52 vorm.

## Technical data

### Hardware Transcoding and Packaging

Hardware Transcoding	
Source Stream Format	SPTS/MPTS MPEG-2 Transport Stream
Source Video Codecs	MPEG-2 and MPEG-4 AVC, 4:2:0
Output Video Codec	MPEG-4 AVC
Source Audio Codecs	AC-3, EC-3, AAC (ADTS & LATM), MPEG 1/2)
Source Audio Channels	7.1, 5.1, 2.0, 1.0
Output Audio Codec	AAC-LC, HE-AAC
Output Audio Channels	2.0, 1.0
Output Streaming	Playlist and Segmentation for HLS Delivery to ABR-capable Set-top Boxes, TVs, Smartphones, Tablets HTTP Live Streaming up to 2 Gbps
DVB Subtitle Burn-in	Select by language

### Service Failover (optional)

Service Failover	Automatic service failover to backup source
Licensed per output	Automatic recovery to primary source Monitor up to 6 parameters in primary source User configurable parameter and duration thresholds
Management and Monitoring	VidiOS™ Web-Based User Interface; Inca All Seeing Eye Compatible; SNMP Trap Forwarding

### Network Interfaces

Management	1000 Base-T
Video input	1000 Base-T
Packaged output	2x 1000 Base-T bonded using LACP

### General data

Supply voltage	100..240 V AC (50/60 Hz)
Power consumption	typ. <75 W
Power supply	2 hot-swappable AC power supplies (Redundancy)
Dimensions (width x height x depth)	431 x 44 x 305 mm
Operating temperature range	0..40 °C
Montage	19", 2 or 4 Post Rack, 1 RU
Weight	4 kg
EMC	FCC Part 15 Class A
Safety standards	CSA/UL 60950-1

## Packaging data

Sales unit	pcs.
Dimensions (WxHxD) sales unit	mm
Packaging volume sales unit	dm³
Gross weight sales unit	kg
Shipping unit	pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm³
Gross weight shipping unit	kg
EAN	4010056755171
Article number	75517