

WISI GI5420 ASE

INCA 5420 ASE Visual Monitoring All Seeing Eye



ELPAS



Description

WISI addresses with its key monitoring solution "All Seeing Eye" cable network operators, City Carriers and Telcos. A major new feature of the "All Seeing Eye" is the new Email alert feature, providing real time email alerts about video impairments to operations staff. The platform facilitates the management and monitoring of all TV channels with video and audio content offered in one network. The SD, HD, MPEG-2 and MPEG-4 Audio/Video streams will be displayed with video thumbnail mosaics on readily-available flat-panel TVs or wall mounted displays. The platform provides detailed stream statistics, including PID and payload details, warnings and errors. By this the technical support team can see all channels in one go and trace impairments through the network with easy click-through to remote system management interfaces.

At a glance:

- MONITOR IP MULTICAST VIDEO
- Thumbnail Mosaic Display
- LOCAL AND REMOTE MONITORING
- VIDIOS™ stream analysis
- CENTRALIZED MANAGEMENT
- Email Notification Service

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern-Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 24. November 2017, 9:52 vorm.

Technical data

VidiOS™ intelligent transport stream monitoring

Input IP from Remote Probe Management Network Interfaces

Stream Analysis MPEG-2 Transport Stream Structure and Display; Transport, Program and Individual PID Bit Rates; Transport Stream Peak and Average Bit Rates; Multiplex, Program and Individual PID Error Detection; Click to Download 10 Second Stream Sample for Offline Analysis

Display

Display Modes Web Based Interactive User Interface; Full Screen Passive Mosaic Wall Mounted Display

Mosaic Features Mosaic of Remote Video Stream Thumbnail Images with Stream Statistics; Visual Remote Alarm Highlighting; Click Through to Single Frame Capture and Download; Click Through from Thumbnail to Remote System Management Interface

Remote Alarm Rollup Remote Probe Transport Stream Alarms in one Place; Click Through from Alarm to Remote System Management Interface

Network Interfaces

Management 1000 Base-T

Secondary network 7x 1000 Base-T

Management functionality

User interfaces Powerful VidiOS™ Web Based User Interface; Rapid Configuration via Automatic Detection of VidiOS Streams; Drag and Drop Mosaic Builder; Multiple Channel Groups

Email Notifications Email Sent When Alarms Occur and When Alarms Clear

General data

Power supply Dual Redundant Hot Swap

Supply voltage 100...240 V AC (50/60 Hz)

Power consumption typ. <120 W

Montage 19", 4 Post Rack, 1 RU, Slide Rails Included

Dimensions (width x height x depth) 431 x 44 x 468 mm (19" x 1,75" x 18,4")

Weight 7 kg (15,4 lb)

Operating temperature range 0...40 °C

EMC FCC Part 15 Class A

Packaging data

Sales unit 1 pcs.

Dimensions (WxHxD) sales unit mm

Packaging volume sales unit dm³

Gross weight sales unit kg

Shipping unit 1 pcs.

Dimensions (WxHxD) shipping unit mm

Packaging volume shipping package dm³

Gross weight shipping unit kg

EAN 4010056744502

Article number 74450

Customs tariff number 85176200